

# TIB393R P. Blue G/S Ink or Automotive Applications

## TECHNICAL DATA SHEET

Technical Specifications	TIB393R
Pigment Code	Pigment 15:4 NCNF (74160)
% Pigment	14%
Strength	100 +/- 2
DE	< 0.5
Weight Per Gallon (lbs)	8.2 +/- 0.2
% Solids	32 +/- 2%
Viscosity, #4 Spindle @ 20 RPM	500 +/- 250
Grind	7+

TIB393R is light and heat stable and can be used in automotive applications as well as outdoor applications. It has been supplied to many of the major USA automotive PVC suppliers for more than 20 years.

		Applications Performance														
		HDPE							PVC-p							
Full Shade	White Reduction	Migration FS 0.1%	Heat FS 0.1%	Heat WR 1:10	Light FS 0.1%	Light WR 1:10	Weather 3000 h FS 0.1%	Weather 3000 h WR 1:10	Warping	Migration FS 0.1%	Light FS 0.1%	Light WR 1:10	Hot light 600 kJ FS 0.1%	Hot light 600 kJ WR 1:10	Weather 5000 h FS 0.1%	Weather 5000 h WR 1:10
		5	300	300	8	8	5	5	L	5	8	8	4-5	4	4	3-4